

SENTRY SIREN

P.O. Box 386
2812 N. 9th St.
Canon City, CO 81212
Tel: 719-275-8691
Fax: 719-269-3397
www.SentrySiren.com

F-2®

117 dB*

Specifications:

117 dB. at 10 ft.
*(outdoor)
113 dB. at 10 ft.
(anechoic chamber)
103 dB. at 10 ft.
(reverberant chamber)
110V AC/DC Motor
1/5 hp. 14,000 rpm Universal
Running Amps: 2.5
U.L Listed
230/250 VAC/DC
(Available on special order)

**Available in 316 Stainless Steel with an
Al-Mag35 Fan and Housing



Thousands of satisfied customers have used this siren in a wide range of industrial, municipal, and a variety of other emergency signaling applications. Recently, the F-2 received full, Grade A Shock Approval by the U.S. Navy and is now standard equipment on all U.S. Navy Battleships.

The F-2 employs a carefully machined and balanced aluminum fan and housing, and aluminum, powder coated projectors. The air intake is screened to protect against foreign matter. Corrosion protected, it is suitable for permanent outdoor installation.

The model F-2 tested at 117 dB. at 10 ft outdoor, 113 dB. at 10 ft. in an anechoic chamber, and at 103 dB(A) in a reverberant room to U.L. Standard 464. The model F-2 runs on 120 volt AC/DC power, with a running amperage of 2.5 amps. With the mounting bracket in the upright position, the F-2 is 15 3/8" long, and 8 1/2" in diameter at its widest point. Shipping weight is 11 pounds.

The Ultimate Utility Siren !!!